

About osFree

What is osFree?

osFree is a [free and open-source](#) operating system based on the [L4](#) microkernel aiming to be binary compatible with [OS/2](#) (ia32). Also, a parallel coexistence of several alien OS API's is possible.

Why use a microkernel

- microkernel can serve as a base for different OS API's, implemented on top of it. These API's can be executed concurrently, having their common part as small as the microkernel is. This allows for parallel (non-layered) implementation of concurrent API's.
- OS API over a microkernel is implemented in user level, leaving only microkernel in privileged kernel mode. Such OS components as thread schedulers, memory managers, swapper task, even direct hardware access and interrupt handling, are moved to userlevel too.
- this allows implementing stable system with rock stable small kernel and less stable user level components, which (as it shows [Minix](#) design, for example) can be restarted (even automatically) after it has failed.
- this also allows to use ordinary development techniques for drivers as driver in microkernel system does not radically differ from other applications.
- microkernel architecture improves dependability of the system, which means that dependencies between system components are well-defined. Servers executing over a microkernel, interact only through well-defined interfaces and encapsulate their internals, which closely resembles the object-oriented approach.
- microkernel system improves isolation of errors inside system components, because servers are executing in separate address spaces.
- microkernel abstracts hardware from usermode servers, which allows implementation of portable operating systems, where all usermode system part remains unchanged in its source form, requiring only its recompilation.

Why L4?

- L4 is a second-generation microkernel, which improves overall system performance significantly. This can be demonstrated by L4Linux as an example. L4Linux is essentially a port of Linux to a new 'L4' architecture. Its hardware access code was changed, so it is accessed not directly, but through L4 mechanisms. The Linux kernel performance can be tested by benchmarks, which shows a loss of about 2% of performance of native Linux kernel. We were tried to start L4Linux on a real machine and did not noticed the difference. This shows that L4 demonstrated excellent performance with very small loss.
- It's minimality and moving all policies outside the kernel, leaving inside it only minimal set of mechanisms, makes it almost universal and makes it possible to implement almost any desired API.
- We're must not reinvent the wheel: it has all required mechanisms, which we need
- A set of general-purpose services is already implemented for it, so we're not left with bare kernel
- L4Linux can be used as Linux personality base. It is yet at development stage but almost all is

working. On our laptop only PCMCIA modem was not working. Wi-fi, bluetooth stack, USB stack, filesystems, CD writing – all these were working!

- Device Driver Environment (DDE) could be used in future as a drivers framework. It ports Linux (DDE/Linux) and FreeBSD (DDE/FreeBSD) drivers to L4 userlevel. So, the big codebase of Linux drivers can be reused in future. In contrast with windows ones, they are available in source form and could be ported to user-level.

Why re-implement OS/2?

OS/2 has one of the most stable, robust and high-performance kernels. Written in assembly language, it is highly-optimized and uses all i386 architecture features very extensively. It's modular design allows to easily replace components with more featured/less resource-eating/cut off GUI, or customize system to fit user preferences. It is highly configurable. We like its compact and clean API, it's easy to use and intuitive powerful true [object-oriented user interface](#). It's uses one of the best general purpose scripting languages named [REXX](#) as operating system scripting service with API available to any application. OS/2 was advertised by IBM as "DOS better than DOS and Windows better than Windows". It is true – it's VDM was the best ever existing. And not only DOS/Windows. It had Java and XFree86 support very powerful too. So, we started loving OS/2 as powerful integration platform on top of single desktop. It has been used by marginals and non-conformists for years and always had its own way. We want to continue following this way :) We can sleep peacefully knowing that it is not popular between hackers and virus writers, they like mainstream.. But we can't stay this way – starting at December 2006, IBM management decided to kill OS/2 and OS/2 community left with aging system without kernel sources and with fading driver support. The driver support becomes more bad each time, and almost all new drivers are ports from Linux. [Petitions](#) to IBM were failed as well. Nevertheless, we want to continue our experience with OS/2. The most necessary task is kernel rewriting. We're always curious regarding IBM's experiments with OS/2 on top of microkernel. We read a readbook about it. So, we meet with enthusiasm the suggestion to use L4 as a base. So this project was started.

Why not migrate to other modern OS?

IBM, Netlabs and other companies tries to move users to another OS like GNU/Linux, BSD, Windows and others. We agree that TCO of current OS/2 become bigger and bigger for home users. In servers area OS/2 also become obsolete (but still stable and mature). But we like approaches of IBM according design of OS. We like it **designed**, not only developed. It is easy to use. It's API is small and clear. We want to continue work and program with OS/2.

Compatible

osFree is planned to be compatible with most of current OS/2 API. But not drivers. OS/2 drivers become more and more obsolete, but we want to have modern hardware support. In current design osFree can be hosted on most of actual kernels like L4, Linux, Windows, etc. As result we can reuse existent drivers as is.

API compatibility allow us to have still clean and small API and reuse existent applications. We have no plan for full support of 16-bit part of OS/2 because not so many applications which true 16-bit. For most mixed 16/32 applications we will provide on-the-fly patching of 16-bit calls to true 32-bit calls. As

result we will have true 32-bit applications (after many years of mixed 16/32 applications).

We have a plan for limited support of DOS and Win16 personalities (for historic reasons). But not limit you to add more personalities.

Lightweight

OS/2 is one of most lightweight 32-bit OS. osFree also will be as lightweight as possible. We don't want to request 1 Gb minimum for work. We want to make it work on as minimal hardware as it possible. This will allow to use osFree in embeded area.

Open

osFree components is comes under open licenses like BSD and (L)GPL licenses. And we try to document interfaces as much as possible. So you are free to extend it as you wish.

Object-oriented

osFree tries to extend object-oriented design of desktop to other parts of the system. We want to introduce CPI+, GPI+, PM+ which is object-oriented representation of current CPI, GPI and PM services. Access to low-level services of the kernel also planned to be represent as objects.

Contributing

We have a lot of things still to do, so any help is welcome. Not only for code development, but also documentation writing, web page maintenance, distribution maintenance, and much more. See the [Project Roadmap](#) for more information about where we intend to go.

We are also looking for developers. For newbies, we have a number of [small tasks](#). If you're an experienced developer, there are plenty of [complex tasks](#) awaiting your talents! Check out the [development page](#) for more information about developing for us, and look at our [licensing](#).

osFree IRC channel is #osFree at [EFnet](#) and [eCSnet](#).

From:
<http://osfree.org/doku/> - **osFree** wiki

Permanent link:
<http://osfree.org/doku/doku.php?id=en:about&rev=1363277120>

Last update: **2013/03/13 23:00**

