



This is part of **Family API** which allow to create dual-os version of program runs under OS/2 and DOS

Note: This is legacy API call. It is recommended to use 32-bit equivalent

2021/09/17 04:47 · prokushev · [0 Comments](#)

2021/08/20 03:18 · prokushev · [0 Comments](#)

KbdPeek

This call returns any available character data record from the keyboard without removing it from the buffer.

Syntax

```
KbdPeek (CharData, KbdHandle)
</cdoe>
```

===== Parameters =====

```
* CharData ([[PKBDKEYINFO]]) - output : Address of the character data
information:
  * asciicharcode ([[UCHAR]]) : ASCII character code. The scan code
received from the keyboard is translated to the ASCII character code.
  * scancode ([[UCHAR]]) : Code received from the keyboard hardware.
  * status ([[UCHAR]]) : State of the keystroke event:

^ Bit ^ Description ^
| 7-6 | 00 = Undefined. |
| :::: | 01 = Final character, interim character flag off. |
| :::: | 10 = Interim character. |
| :::: | 11 = Final character, interim character flag on. |
| 5 | 1 = Immediate conversion requested. |
| 4-2 | Reserved, set to zero. |
| 1 | 0 = Scan code is a character. |
| :::: | 1 = Scan code is not a character; it is an extended key code from
the keyboard. |
| 0 | 1 = Shift status returned without character. |

  * reserved ([[UCHAR]]) : NLS shift status. Reserved, set to zero.
  * shiftkeystat ([[USHORT]]) : Shift key status.

^ Bit ^ Description ^
| 15 | SysReq key down |
| 14 | CapsLock key down |
| 13 | NumLock key down |
```

```

| 12 | ScrollLock key down |
| 11 | Right Alt key down |
| 10 | Right Ctrl key down |
| 9 | Left Alt key down |
| 8 | Left Ctrl key down |
| 7 | Insert on |
| 6 | CapsLock on |
| 5 | NumLock on |
| 4 | ScrollLock on |
| 3 | Either Alt key down |
| 2 | Either Ctrl key down |
| 1 | Left Shift key down |
| 0 | Right Shift key down |

```

* time ([[ULONG]]) : Time stamp indicating when a key was pressed. It is specified in milliseconds from the time the system was started.

* KbdHandle ([[HKBD]]) - input : Default keyboard or the logical keyboard.

===== Return Code =====

rc ([[USHOR]]T) - return

Return code descriptions are:

- * 0 NO_ERROR
- * 439 ERROR_KBD_INVALID_HANDLE
- * 445 ERROR_KBD_FOCUS_REQUIRED
- * 447 ERROR_KBD_KEYBOARD_BUSY
- * 464 ERROR_KBD_DETACHED
- * 504 ERROR_KBD_EXTENDED_SG

===== Remarks =====

On an enhanced keyboard, the secondary enter key returns the normal character 0DH and a scan code of E0H.

Double-byte character codes (DBCS) require two function calls to obtain the entire code.

If shift report is set with KbdSetStatus the CharData record returned, reflects changed shift information only.

Extended ASCII codes are identified with the status byte, bit 1 on and the ASCII character code being either 00H or E0H. Both conditions must be satisfied for the character to be an extended keystroke. For extended ASCII codes, the scan code byte returned is the second code (extended code). Usually the extended ASCII code is the scan code of the primary key that was pressed.

A thread in the foreground session that repeatedly polls the keyboard with KbdCharIn (with no wait), can prevent all regular priority class threads

from executing. If polling must be used and a minimal amount of other processing is being performed, the thread should periodically yield the CPU by issuing a DosSleep call for an interval of at least 5 milliseconds.

===== Family API Considerations =====

Some options operate differently in the DOS mode than in the OS/2 mode. Therefore, the following restrictions apply to KbdPeek when coding for the DOS mode:

- * The CharData structure includes everything except the time stamp.
- * Interim character is not supported.
- * Status can be 0 or 1.
- * KbdHandle is ignored.

===== Bindings =====

=====C Binding=====

```
<code c>
typedef struct _KBDKEYINFO { /* kbci */
    UCHAR    chChar;           /* ASCII character code */
    UCHAR    chScan;          /* Scan Code */
    UCHAR    fbStatus;        /* State of the character */
    UCHAR    bNlsShift;       /* Reserved (set to zero) */
    USHORT   fsState;         /* State of the shift keys */
    ULONG    time;             /* Time stamp of keystroke (ms since ipl) */
}KBDKEYINFO;

#define INCL_KBD

USHORT  rc = KbdPeek(CharData, KbdHandle);

PKBDKEYINFO      CharData;      /* Buffer for data */
HKBD             KbdHandle;    /* Keyboard handle */

USHORT           rc;           /* return code */
```

MASM Binding

```
KBDKEYINFO  struct
    kbci_chChar    db  ? ;ASCII character code
    kbci_chScan    db  ? ;Scan Code
    kbci_fbStatus  db  ? ;State of the character
    kbci_bNlsShift db  ? ;Reserved (set to zero)
    kbci_fsState   dw  ? ;state of the shift keys
    kbci_time      dd  ? ;time stamp of keystroke (ms since ipl)
KBDKEYINFO ends

EXTRN  KbdPeek:FAR
INCL_KBD          EQU 1
```

```
PUSH@ OTHER CharData      ;Buffer for data
PUSH WORD   KbdHandle    ;Keyboard handle
CALL     KbdPeek
```

Returns **WORD**

Note

Text based on [http://www.edm2.com/index.php/KbdPeek_\(FAPI\)](http://www.edm2.com/index.php/KbdPeek_(FAPI))

Family API		
DOS	Process Manager	DosBeep DosExit DosSleep DosExecPgm
	File Manager	DosChDir DosChgFilePtr DosClose DosDelete DosDupHandle DosMkDir DosMove DosQCurDir DosQCurDisk DosSet FileMode DosOpen DosQFileInfo DosRead DosQ FileMode DosQFSInfo DosQVerify DosRmDir DosSelectDisk DosFindClose DosFindFirst DosFindNext DosSet FileInfo DosSet Verify DosWrite DosFileLocks DosSet FHandState DosNewSize DosBufReset DosQFHandState DosSet FSInfo
	Memory Manager	DosFreeSeg DosSubAlloc DosSubFree DosSubSet DosAlloc Huge DosAlloc Seg DosRealloc Huge DosRealloc Seg DosGet Huge Shift DosCreate CS Alias
	NLS	DosCaseMap DosGet Ctry Info DosGet DBCSEv DosSet Ctry Code DosGet Collate DosGet Message DosIns Message DosPut Message
	Date and Time	DosSet Date Time DosGet Date Time
	Devices	DosDevConfig DosDevIOCtl DosDevIOCtl2
	Signals	DosHold Signal DosSet Sig Handler
	Misc	BadDynLink DosGet Env DosGet Machine Mode DosGet Version DosError DosErr Class DosSet Vec
KBD		KbdCharIn KbdFlush Buffer KbdGet Status KbdSet Status KbdStringIn KbdPeek
VIO		VioGet Buf VioGet Config VioGet Cur Pos VioGet Cur Type VioGet Phys Buf VioRead Cell Str VioRead Char Str VioScroll Up VioScroll Dn VioScroll If VioScroll Rt VioScr Un Lock VioSet Cur Pos VioSet Cur Type VioSet Mode VioGet Mode VioShow Buf VioWrt Cell Str VioWrt Char Str VioWrt Char Str Att VioWrt N Attr VioWrt N Cell VioWrt N Char VioWrt TTY VioScr Lock VioPop Up
Tools		BIND
Modules		DOSCALLS.DLL VIOCALS.DLL KBDCALLS.DLL MSG.DLL
Libraries		API.LIB OS2386.LIB FAPI.LIB DOSCALLS.LIB SUBCALLS.LIB

2018/08/25 15:05 · prokushev · 0 Comments

From:
<http://osfree.org/doku/> - osFree wiki

Permanent link:
<http://osfree.org/doku/doku.php?id=en:docs:fapi:kbdpeek&rev=1632015462>

Last update: **2021/09/19 01:37**

