



This is part of **Family API** which allow to create dual-os version of program runs under OS/2 and DOS

Note: This is legacy API call. It is recommended to use 32-bit equivalent

2021/09/17 04:47 · prokushev · [0 Comments](#)

2021/08/20 03:18 · prokushev · [0 Comments](#)

VioGetMode

This call returns the mode of the display.

Syntax

```
VioGetMode (ModeData, VioHandle)
```

Parameters

- ModeData ([PVIOMODEINFO](#)) - input/output : Far address of a structure where mode characteristics are returned.
- VioHandle ([HVIO](#)) - input : Reserved word of 0s.

Return Code

rc ([USHORT](#)) - return

Return code descriptions are:

- 0 NO_ERROR
- 436 ERROR_VIO_INVALID_HANDLE
- 438 ERROR_VIO_INVALID_LENGTH
- 465 ERROR_VIO_DETACHED
- 494 ERROR_VIO_EXTENDED_SG

Remarks

Refer to [VioSetMode](#) for examples.

Bindings

C

```
typedef struct _VIOMODEINFO {
    USHORT cb; /* Length of the entire data structure */
    UCHAR fbType; /* Bit mask of mode being set */
    UCHAR color; /* Number of colors (power of 2) */
    USHORT col; /* Number of text columns */
    USHORT row; /* Number of text rows */
    USHORT hres; /* Horizontal resolution */
    USHORT vres; /* Vertical resolution */
    UCHAR fmt_ID; /* Attribute format */
    UCHAR attrib; /* Number of attributes */
    ULONG buf_addr;
    ULONG buf_length;
    ULONG full_length;
    ULONG partial_length;
    PCH ext_data_addr;
} VIOMODEINFO;
typedef VIOMODEINFO far *PVIOMODEINFO;

#define INCL_VIO

USHORT rc = VioGetMode(ModeData, VioHandle);

PVIOMODEINFO ModeData; /* Mode characteristics */
HVIO VioHandle; /* Vio handle */

USHORT rc; /* return code */
```

MASM

```
VIOMODEINFO struc
    viomi_cb dw ? ;Length of the entire data structure
    viomi_fbType db ? ;Bit mask of mode being set
    viomi_color db ? ;Number of colors (power of 2)
    viomi_col dw ? ;Number of text columns
    viomi_row dw ? ;Number of text rows
    viomi_hres dw ? ;Horizontal resolution
    viomi_vres dw ? ;Vertical resolution
    viomi_fmt_ID db ? ;Attribute format
    viomi_attrib db ? ;Number of attributes
    viomi_buf_addr dd ? ;
    viomi_buf_length dd ? ;
    viomi_full_length dd ? ;
    viomi_partial_length dd ? ;
    viomi_ext_data_addr dd ? ;
```

VIOMODEINFO ends

EXTRN VioGetMode:FAR

INCL_VIO EQU 1

PUSH@ OTHER ModeData ;Mode characteristics

PUSH WORD VioHandle ;Vio handle

CALL VioGetMode

Returns WORD

Family API

DOS	Process Manager	DosBeep DosExit DosSleep DosExecPgm
	File Manager	DosChDir DosChgFilePtr DosClose DosDelete DosDupHandle DosMkDir DosMove DosQCurDir DosQCurDisk DosSetFileMode DosOpen DosQFileInfo DosRead DosQFileMode DosQFSInfo DosQVerify DosRmdir DosSelectDisk DosFindClose DosFindFirst DosFindNext DosSetFileInfo DosSetVerify DosWrite DosFileLocks DosSetFHandState DosNewSize DosBufReset DosQFHandState DosSetFSinfo
	Memory Manager	DosFreeSeg DosSubAlloc DosSubFree DosSubSet DosAllocHuge DosAllocSeg DosReallocHuge DosReallocSeg DosGetHugeShift DosCreateCSAlias
	NLS	DosCaseMap DosGetCtryInfo DosGetDBCSEv DosSetCtryCode DosGetCollate DosGetMessage DosInsMessage DosPutMessage
	Date and Time	DosSetDateTime DosGetDateTime
	Devices	DosDevConfig DosDevIOctl DosDevIOctl2
	Signals	DosHoldSignal DosSetSigHandler
	Misc	BadDynLink DosGetEnv DosGetMachineMode DosGetVersion DosError DosErrClass DosSetVec
KBD		KbdCharIn KbdFlushBuffer KbdGetStatus KbdSetStatus KbdStringIn KbdPeek
VIO		VioGetBuf VioGetConfig VioGetCurPos VioGetCurType VioGetPhysBuf VioReadCellStr VioReadCharStr VioScrollUp VioScrollDn VioScrollLf VioScrollRt VioScrUnLock VioSetCurPos VioSetCurType VioSetMode VioGetMode VioShowBuf VioWrtCellStr VioWrtCharStr VioWrtCharStrAtt VioWrtNAttr VioWrtNCell VioWrtNChar VioWrtTTY VioScrLock VioPopUp
Tools		BIND
Modules		DOSCALLS.DLL VIOCALLS.DLL KBDSCALLS.DLL MSG.DLL
Libraries		API.LIB OS2386.LIB FAPI.LIB DOSCALLS.LIB SUBCALLS.LIB

2018/08/25 15:05 · prokushev · 0 Comments

From:

<http://osfree.org/doku/> - osFree wiki

Permanent link:

<http://osfree.org/doku/doku.php?id=en:docs:fapi:viogetmode>

Last update: 2021/09/19 04:48

