2025/10/16 13:00 1/2 Build level information

# **Build level information**

Any osFree executibles contains build level information string. Usually build level placed into resources, but also can be in code or data sections.

Usual place of build level information is Description string of DEF-file:

```
Description '@#osFree:9.23#@Control utility for ANSI'
```

## Minimal build level information

Commonly used following build level information syntax:

```
@#<Vendor>:<Revision>#@<Description>
```

where <Vendor>, <Revision> and <Description> are ascii strings with corresponding information. In EDM/2 http://www.edm2.com/index.php/Adding\_BLDLEVEL\_information\_to\_executables mentioned some restrictions for <Vendor>, <Revision> and <Description>, but actually length can be any and version format can be any. As example can be pointed some OS2KRNL revisions.

Example:

```
Description '@#osFree:9.23#@Control utility for ANSI'
```

## Extended build level information Type I

MPTN and TCP/IP services of osFree uses extended build level information. In most cases such information not stored as Description, but as asciiz constant string in code. This is why standard OS/2 bldlevel tool does not work for such files. Syntax is following:

```
@#<Vendor>:<Revision>#@##built <BuildDate> - on
<BuildHost>;0.1@@<Description>[:<SubDescription>[:<SubDescription>...]
```

#### where

- <BuildDate> is date and time of build
- <BuildHost> is machine on which build compiled
- <SubDescription> is closer description of software pack

### Example:

```
Description '@#osFree:9.23#@##build 5 Oct 2003 15:00:00 — on RACERPC;0.1@@Command line tools:Control utility for ANSI'
```

# **Extended build level information Type II**

Another most known, and most complex, type of build level information is following:

```
@#<Vendor>:<Revision>#@1## DD.MM.YY hh:mm:ss
<BuildHost>:<ASDFeatureID>:<LanguageCode>:<CountryCode>:<Build>:<Unknown>:<F
ixPackVer>@@<Description>
```

### where

- DD.MM.YY is the build date in day/month/year, preceded by 1 space
- hh:mm:ss is the build time in hour/minute/second, preceded by 1 space
- <BuildHost> is machine on which build compiled, preceded by 8 spaces
- <ASDFeatureID> is identifier of ASD feature
- <LanguageCode> is code of language of component
- <CountryCode> is country code of component
- <Build> is build number
- <Unknown> is not known information (must be empty)
- <FixPackVer> is FixPack version (if distibuted as part of).

Note: If you leave build date and/or build time empty you still have to provide the same amount of spaces to replace build date/build time.

## Example:

```
Description '@#osFree:9.23#@##1##RACERPC:0:866:7:436::WRR8706@@Control utility for ANSI'
```

Nowdays many projects use this BLDLEVEL format string.

### **Related links**

Adding BLDLEVEL information to executables

From:

http://osfree.org/doku/ - osFree wiki

Permanent link:

http://osfree.org/doku/doku.php?id=en:docs:os2:bld:index&rev=1403644403

Last update: 2014/06/24 21:13



http://osfree.org/doku/ Printed on 2025/10/16 13:00