

# Keyboard Function Calls

This section reflects the Keyboard API interface of OS/2 only.

For information regarding the keyboard IOCTL interface and keyboard monitor refer to IBM Operating System/2 Version 1.2 I/O Subsystems And Device Support Volume 1.

## Notes:

1. Calls marked xPM are not supported by Presentation Manager, and must not be used by Presentation Manager applications. An error code is returned if any of these calls are issued.
2. Calls marked xWPM are not windowable and are not supported by Presentation Manager. They can be used in OS/2 mode.
3. Calls marked FAPI are present in the Family API.

FUNCTION CALL	ICON	Description
<a href="#">KbdCharIn</a>	FAPI xPM	This call returns a character data record from the keyboard.
<a href="#">KbdClose</a>	xPM	This call closes the existing logical keyboard identified by the keyboard handle.
<a href="#">KbdDeRegister</a>	xWPM	This call deregisters a keyboard subsystem previously registered within a session.
<a href="#">KbdFlushBuffer</a>	FAPI xPM	
<a href="#">KbdFreeFocus</a>	xPM	This call frees the logical-to-physical keyboard bond created by KbdGetFocus
<a href="#">KbdGetCp</a>	xPM	
<a href="#">KbdGetFocus</a>	xPM	
<a href="#">KbdGetStatus</a>	FAPI xPM	
<a href="#">KbdOpen</a>	xPM	
<a href="#">KbdPeek</a>	FAPI xPM	
<a href="#">KbdRegister</a>	xWPM	This call registers a keyboard subsystem within a session.
<a href="#">KbdSetCp</a>	xPM	
<a href="#">KbdSetCustXt</a>	xPM	
<a href="#">KbdSetFgnd</a>	xPM	
<a href="#">KbdSetStatus</a>	FAPI xPM	
<a href="#">KbdStringIn</a>	FAPI xPM	
<a href="#">KbdSynch</a>	xWPM	
<a href="#">KbdXlate</a>	xPM	

From:

<http://osfree.org/doku/> - **osFree wiki**

Permanent link:

<http://osfree.org/doku/doku.php?id=en:ibm:prcp:kbd&rev=1399992196>

Last update: **2014/05/13 14:43**

