

This call is used to set the date and time that are maintained by the operating system.

## Syntax

DosSetDateTime (DateTime)

## Parameters

;DateTime (PDATETIME) - input : Address of the date and time structure: ::hours (UCHAR) - Current hour (0-23) ::minutes (UCHAR) - Current minute (0-59) ::seconds (UCHAR) - Current second (0-59) ::hundredths (UCHAR) - Current hundredth of a second (0-99) ::day (UCHAR) - Current day (1-31) ::month (UCHAR) - Current month (1-12) ::year (USHORT) - Current year (1980-2079) ::timezone (SHORT) - Minutes west of UTC (Universal Time Coordinate -720 to 720). ::weekday (UCHAR) - Current day of the week. This value is ignored and is calculated from the other parameter information.

## Return Code

rc (USHORT) - return Return code descriptions are: \* 0 NO\_ERROR \*327 ERROR\_TS\_DATETIME

## Remarks

The value of timezone is the difference in minutes between the current time zone and UTC. This is a positive number if earlier than UTC, and negative number if it is later. For Eastern Standard Time this value is 300 (five hours earlier than UTC).

To get the date and time, issue DosGetDateTime. If the application is executing in the OS/2 environment, it is more efficient to obtain these variables by calling DosGetInfoSeg instead of this function. However, applications written to the family API cannot depend on the availability of DosGetInfoSeg.

Not adhering to the limits on any of the parameters results in the return code being set to rc = 327 (ERROR\_TS\_DATETIME). Also, OS/2 verifies that the day is possible for the month and the year (even for leap year). If the day is not reasonable, OS/2 will also set rc = 327.

## Example Code

## C Binding

```
<PRE> typedef struct _DATETIME { /* date */
```

```
    UCHAR    hours;           /* current hour */
    UCHAR    minutes;        /* current minute */
    UCHAR    seconds;        /* current second */
    UCHAR    hundredths;     /* current hundredths of a second */
```

```
UCHAR   day;           /* current day */
UCHAR   month;        /* current month */
USHORT  year;         /* current year */
SHORT   timezone;    /* minutes of time west of UTC */
UCHAR   weekday;     /* current day of week */
```

```
} DATETIME;
```

```
#define INCL_DOSDATETIME
```

USHORT rc = DosSetDateTime(DateTime); PDATETIME DateTime; /\* Date/time structure \*/ USHORT rc;  
/\* return code \*/ </PRE> The following example obtains and prints date and time information. It then  
changes the system date to 5/10/1987 and prints the updated information. <PRE> #define  
INCL\_DOSDATETIME #include <os2.h>

```
main() {
```

```
DATETIME   DateTime;      /* Structure to hold date/time info. */
USHORT     rc;
```

```
rc = DosGetDateTime(&DateTime);    /* Address of d/t structure */
printf("Today is %d-%d-%d; the time is %d:%d\n", DateTime.month,
       DateTime.day, DateTime.year, DateTime.hours, DateTime.minutes);
DateTime.day = 10;
DateTime.month = 5;
DateTime.year = 1987;
printf("The new date is %d-%d-%d; the time is %d:%d\n", DateTime.month,
       DateTime.day, DateTime.year, DateTime.hours, DateTime.minutes);
rc = DosSetDateTime(&DateTime);    /* Address of d/t structure */
printf("rc is %d\n", rc);
```

```
} </PRE>
```

## MASM Binding

```
<pre> DATETIME struc
```

```
date_hours      db  ? ;current hour
date_minutes    db  ? ;current minute
date_seconds    db  ? ;current second
date_hundredths db  ? ;current hundredths of a second
date_day        db  ? ;current day
date_month      db  ? ;current month
date_year       dw  ? ;current year
date_timezone   dw  ? ;minutes of time west of UTC
date_weekday    db  ? ;current day of week
```

```
DATETIME ends
```

EXTRN DosSetDateTime:FAR INCL\_DOSDATETIME EQU 1

PUSH@ OTHER DateTime ;Date/time structure CALL DosSetDateTime

Returns WORD </pre>

# Note

Text based on [http://www.edm2.com/index.php/DosSetDateTime\\_\(Legacy\)](http://www.edm2.com/index.php/DosSetDateTime_(Legacy))

Family API		
DOS	Process Manager	DosBeep DosExit DosSleep DosExecPgm
	File Manager	DosChDir DosChgFilePtr DosClose DosDelete DosDupHandle DosMkDir DosMove DosQCurDir DosQCurDisk DosSetFileMode DosOpen DosQFileInfo DosRead DosQFileMode DosQFSInfo DosQVerify DosRmDir DosSelectDisk DosFindClose DosFindFirst DosFindNext DosSetFileInfo DosSetVerify DosWrite DosFileLocks DosSetFHandState DosNewSize DosBufReset DosQFHandState DosSetFSInfo
	Memory Manager	DosFreeSeg DosSubAlloc DosSubFree DosSubSet DosAllocHuge DosAllocSeg DosReallocHuge DosReallocSeg DosGetHugeShift DosCreateCSAlias
	NLS	DosCaseMap DosGetCtryInfo DosGetDBCSEv DosSetCtryCode DosGetCollate DosGetMessage DosInsMessage DosPutMessage
	Date and Time	DosSetDateTime DosGetDateTime
	Devices	DosDevConfig DosDevIOct1 DosDevIOct2
	Signals	DosHoldSignal DosSetSigHandler
	Misc	BadDynLink DosGetEnv DosGetMachineMode DosGetVersion DosError DosErrClass DosSetVec
KBD	KbdCharIn KbdFlushBuffer KbdGetStatus KbdSetStatus KbdStringIn KbdPeek	
VIO	VioGetBuf VioGetConfig VioGetCurPos VioGetCurType VioGetPhysBuf VioReadCellStr VioReadCharStr VioScrollUp VioScrollDn VioScrollLf VioScrollRt VioScrUnLock VioSetCurPos VioSetCurType VioSetMode VioGetMode VioShowBuf VioWrtCellStr VioWrtCharStr VioWrtCharStrAtt VioWrtNAttr VioWrtNCell VioWrtNChar VioWrtTTY VioScrLock VioPopUp	
Tools	BIND	
Modules	DOSCALLS.DLL VIOCALLS.DLL KBDCALLS.DLL MSG.DLL	
Libraries	API.LIB OS2386.LIB FAPI.LIB DOSCALLS.LIB SUBCALLS.LIB	

2018/08/25 15:05 · prokushev · 0 Comments

From: <https://osfree.org./doku/> - **osFree wiki**

Permanent link: <https://osfree.org./doku/doku.php?id=en:docs:fapi:dossetdatetime&rev=1535700300>

Last update: **2018/08/31 07:25**

