



This is part of **Family API** which allow to create dual-os version of program runs under OS/2 and DOS

Note: This is legacy API call. It is recommended to use 32-bit equivalent

2021/09/17 04:47 · prokushev · [0 Comments](#)

2021/08/20 03:18 · prokushev · [0 Comments](#)

KbdSetStatus

This call sets the characteristics of the keyboard.

Syntax

```
KbdSetStatus (StatData, KbdHandle)
```

Parameters

- StatData ([PKBDINFO](#)) - input : Address of the keyboard status structure:
 - length ([USHORT](#)) : Length, in bytes, of this data structure, including length.
 - 10 - Only valid value.
 - sysstate ([USHORT](#)) : The system state altered by this call. If bits 0 and 1 are off, the echo state of the system is not altered. If bits 2 and 3 are off, the binary and ASCII state of the system is not altered. If bits 0 and 1 are on, or if bits 2 and 3 are on, the function returns an error. If binary mode is set, echo is ignored.

Bit	Description
15-9	Reserved, set to zero
8	Shift return is on
7	Length of the turn-around character (meaningful only if bit 6 is on).
6	Turn-around character is modified
5	Interim character flags are modified
4	Shift state is modified
3	ASCII mode is on
2	Binary mode is on
1	Echo off
0	Echo on

- turnchardef ([USHORT](#)) : Definition of the turn-around character. In ASCII and extended-ASCII format, the turn-around character is defined as the carriage return. In ASCII format only, the turn-around character is defined in the low-order byte.
- intcharflag ([USHORT](#)) : Interim character flags:

Bit	Description
15-8	NLS shift state.
7	Interim character flag is on
6	Reserved, set to zero
5	Application requested immediate conversion
4-0	Reserved, set to zero

- shiftstate ([USHORT](#)) : Shift state.

Bit	Description
15	SysReq key down
14	CapsLock key down
13	NumLock key down
12	ScrollLock key down
11	Right Alt key down
10	Right Ctrl key down
9	Left Alt key down
8	Left Ctrl key down
7	Insert on
6	CapsLock on
5	NumLock on
4	ScrollLock on
3	Either Alt key down
2	Either Ctrl key down
1	Left Shift key down
0	Right Shift key down

- KbdHandle ([HKBD](#)) - input : Default keyboard or the logical keyboard.

Return Code

rc ([USHORT](#)) - return

Return code descriptions are:

- 0 NO_ERROR
- 376 ERROR_KBD_INVALID_LENGTH
- 377 ERROR_KBD_INVALID_ECHO_MASK
- 378 ERROR_KBD_INVALID_INPUT_MASK
- 439 ERROR_KBD_INVALID_HANDLE
- 445 ERROR_KBD_FOCUS_REQUIRED
- 447 ERROR_KBD_KEYBOARD_BUSY
- 464 ERROR_KBD_DETACHED
- 504 ERROR_KBD_EXTENDED_SG

Remarks

Shift return (bit 8 in sysstate) must be disabled in ASCII mode.

KbdSetStatus is ignored for a Vio-windowed application.

Family API Considerations

Some options operate differently in the DOS mode than in the OS/2 mode. Therefore, the following restrictions apply to KbdSetStatus when coding in the DOS mode:

- KbdSetStatus does not accept a bit mask of 10 (ASCII on, Echo Off).
- Raw (binary) Mode and Echo On are not supported and return an error if requested.
- KbdHandle is ignored.
- Interim character is not supported.
- Turnaround character is not supported.

Bindings

C Binding

```
typedef struct _KBDINFO {          /* kbst */
    USHORT cb;                    /* length in bytes of this structure */
    USHORT fsMask;               /* bit mask of functions to be altered */
    USHORT chTurnAround;        /* define TurnAround character */
    USHORT fsInterim;           /* interim character flags */
    USHORT fsState;             /* shift states */
}KBDINFO;

#define INCL_KBD

USHORT rc = KbdSetStatus(Structure, KbdHandle);

PKBDINFO      Structure;        /* Data structure */
HKBD          KbdHandle;       /* Keyboard Handle */

USHORT        rc;              /* return code */
```

MASM Binding

```
KBDINFO struc
    kbst_cb          dw ? ;length in bytes of this structure
    kbst_fsMask     dw ? ;bit mask of functions to be altered
    kbst_chTurnAround dw ? ;define TurnAround character
    kbst_fsInterim  dw ? ;interim character flags
```

```

    kbst_fsState      dw ? ;shift states
KBDINFO ends

EXTRN KbdSetStatus:FAR
INCL_KBD      EQU 1

PUSH@ OTHER Structure ;Data structure
PUSH WORD KbdHandle ;Keyboard Handle
CALL KbdSetStatus


Returns WORD
    
```

Note

Text based on [http://www.edm2.com/index.php/KbdSetStatus_\(FAP\)](http://www.edm2.com/index.php/KbdSetStatus_(FAP))

Family API		
DOS	Process Manager	DosBeep DosExit DosSleep DosExecPgm
	File Manager	DosChDir DosChgFilePtr DosClose DosDelete DosDupHandle DosMkDir DosMove DosQCurDir DosQCurDisk DosSetFileMode DosOpen DosQFileInfo DosRead DosQFileMode DosQFSInfo DosQVerify DosRmdir DosSelectDisk DosFindClose DosFindFirst DosFindNext DosSetFileInfo DosSetVerify DosWrite DosFileLocks DosSetFHandState DosNewSize DosBufReset DosQFHandState DosSetFSInfo
	Memory Manager	DosFreeSeg DosSubAlloc DosSubFree DosSubSet DosAllocHuge DosAllocSeg DosReallocHuge DosReallocSeg DosGetHugeShift DosCreateCSAlias
	NLS	DosCaseMap DosGetCtryInfo DosGetDBCSEv DosSetCtryCode DosGetCollate DosGetMessage DosInsMessage DosPutMessage
	Date and Time	DosSetDateTime DosGetDateTime
	Devices	DosDevConfig DosDevIOct1 DosDevIOct2
	Signals	DosHoldSignal DosSetSigHandler
	Misc	BadDynLink DosGetEnv DosGetMachineMode DosGetVersion DosError DosErrClass DosSetVec
KBD	KbdCharIn KbdFlushBuffer KbdGetStatus KbdSetStatus KbdStringIn KbdPeek	
VIO	VioGetBuf VioGetConfig VioGetCurPos VioGetCurType VioGetPhysBuf VioReadCellStr VioReadCharStr VioScrollUp VioScrollDn VioScrollLf VioScrollRt VioScrUnLock VioSetCurPos VioSetCurType VioSetMode VioGetMode VioShowBuf VioWrtCellStr VioWrtCharStr VioWrtCharStrAtt VioWrtNAttr VioWrtNCell VioWrtNChar VioWrtTTY VioScrLock VioPopUp	
Tools	BIND	
Modules	DOSCALLS.DLL VIOCALLS.DLL KBDCALLS.DLL MSG.DLL	
Libraries	API.LIB OS2386.LIB FAPI.LIB DOSCALLS.LIB SUBCALLS.LIB	

2018/08/25 15:05 · prokushev · 0 Comments



From:

<https://osfree.su/doku/> - **osFree wiki**

Permanent link:

<https://osfree.su/doku/doku.php?id=en:docs:fapi:kbdsetstatus>

Last update: **2021/09/19 01:27**

