

KbdFreeFocus

Bindings:

C:

```
#define INCL_KBD

USHORT rc = KbdFreeFocus(KbdHandle);

HKBD KbdHandle; /* Keyboard handle */

USHORT rc; /* return code */
```

MASM:

```
EXTRN KbdFreeFocus:FAR
INCL_KBD EQU 1

PUSH WORD KbdHandle ;Keyboard handle
CALL KbdFreeFocus

Returns WORD
```

This call frees the logical-to-physical keyboard bond created by [KbdGetFocus](#).

KbdFreeFocus (KbdHandle)

KbdHandle (**HKBD**) - input Default keyboard or the logical keyboard.

rc (**USHORT**) - return Return code descriptions are:

0	NO_ERROR
439	ERROR_KBD_INVALID_HANDLE
445	ERROR_KBD_FOCUS_REQUIRED
464	ERROR_KBD_DETACHED
504	ERROR_KBD_EXTENDED_SG

Remarks

KbdFreeFocus may be replaced by issuing [KbdRegister](#). Unlike other keyboard subsystem functions, the replaced *KbdFreeFocus* is called only if there is an outstanding focus.

From: <https://osfree.org./doku/> - **osFree wiki**

Permanent link: <https://osfree.org./doku/doku.php?id=en.ibm:prcp:kbd:freefocus&rev=1399991361>

Last update: **2014/05/13 14:29**



