

Keyboard Function Calls

This section reflects the Keyboard API interface of OS/2 only.

For information regarding the keyboard IOCTL interface and keyboard monitor refer to IBM Operating System/2 Version 1.2 I/O Subsystems And Device Support Volume 1.

Notes:

1. Calls marked xPM are not supported by Presentation Manager, and must not be used by Presentation Manager applications. An error code is returned if any of these calls are issued.
2. Calls marked xWPM are not windowable and are not supported by Presentation Manager. They can be used in OS/2 mode.
3. Calls marked FAPI are present in the Family API.

FUNCTION CALL	ICON	Description
KbdCharIn	FAPI xPM	This call returns a character data record from the keyboard.
KbdClose	xPM	This call closes the existing logical keyboard identified by the keyboard handle.
KbdDeRegister	xWPM	This call deregisters a keyboard subsystem previously registered within a session.
KbdFlushBuffer	FAPI xPM	
KbdFreeFocus	xPM	
KbdGetCp	xPM	
KbdGetFocus	xPM	
KbdGetStatus	FAPI xPM	
KbdOpen	xPM	
KbdPeek	FAPI xPM	
KbdRegister	xWPM	
KbdSetCp	xPM	
KbdSetCustXt	xPM	
KbdSetFgnd	xPM	
KbdSetStatus	FAPI xPM	
KbdStringIn	FAPI xPM	
KbdSynch	xWPM	
KbdXlate	xPM	

From:

<https://osfree.org./doku/> - **osFree wiki**

Permanent link:

<https://osfree.org./doku/doku.php?id=en:ibm:prcp:kbd&rev=1399990599>

Last update: **2014/05/13 14:43**

