



This is part of **Family API** which allow to create dual-os version of program runs under OS/2 and DOS

**Note:** This is legacy API call. It is recommended to use 32-bit equivalent

2021/09/17 04:47 · prokushev · [0 Comments](#)

2021/08/20 03:18 · prokushev · [0 Comments](#)

## KbdFreeFocus

This call frees the logical-to-physical keyboard bond created by [KbdGetFocus](#).

### Syntax

```
KbdFreeFocus (KbdHandle)
```

### Parameters

- KbdHandle (HKBD) - input: Default keyboard or the logical keyboard.

### Return Code

rc (USHORT) - return:Return code descriptions are:

- 0 NO\_ERROR
- 439 ERROR\_KBD\_INVALID\_HANDLE
- 445 ERROR\_KBD\_FOCUS\_REQUIRED
- 464 ERROR\_KBD\_DETACHED
- 504 ERROR\_KBD\_EXTENDED\_SG

### Remarks

KbdFreeFocus may be replaced by issuing [KbdRegister](#). Unlike other keyboard subsystem functions, the replaced KbdFreeFocus is called only if there is an outstanding focus.

### Bindings

## C

```
#define INCL_KBD

USHORT rc = KbdFreeFocus(KbdHandle);
HKBD KbdHandle; /* Keyboard handle */

USHORT rc; /* return code */
```

## MASM

```
EXTRN KbdFreeFocus:FAR
INCL_KBD EQU 1

PUSH WORD KbdHandle ;Keyboard handle
CALL KbdFreeFocus

Returns WORD
```

From:  
<https://osfree.org/doku/> - osFree wiki

Permanent link:  
<https://osfree.org/doku/doku.php?id=en:docs:fapi:kbdfreefocus&rev=1634998922>

Last update: 2021/10/23 14:22

