

MouClose closes the mouse device for the current session and removes the mouse device driver handle from the list of valid open mouse device handles.

Syntax

MouClose (DeviceHandle)

Parameters

;DeviceHandle (HMOU) - input : Mouse device handle from a previous MouOpen.

Return Code

;rc (USHORT) - return:Return code descriptions are: * 0 - NO_ERROR * 385 - ERROR_MOUSE_NO_DEVICE * 466 - ERROR_MOU_DETACHED * 501 - ERROR_MOUSE_NO_CONSOLE * 505 - ERROR_MOU_EXTENDED_SG

Bindings

C

```
<PRE> #define INCL_MOUSE
```

```
USHORT rc = MouClose(DeviceHandle);
```

```
HMOU DeviceHandle; /* Mouse device handle */ USHORT rc; /* return code */ </PRE>
```

MASM

```
<PRE> EXTRN MouClose:FAR INCL_MOUSE EQU 1
```

```
PUSH WORD DeviceHandle ;Mouse device handle CALL MouClose
```

```
Returns WORD </PRE>
```

Mou

From:

<https://osfree.org/doku/> - **osFree wiki**

Permanent link:

<https://osfree.org/doku/doku.php?id=en:docs:fapi:mouclose&rev=1633614256>

Last update: **2021/10/07 13:44**



