

This call directs the mouse driver to flush (empty) the mouse event queue and the monitor chain data for the session.

### Syntax

MouFlushQue (DeviceHandle)

### Parameters

;DeviceHandle (HMOU) - input : Mouse device handle from a previous MouOpen.

### Return Code

;rc (USHORT) - return:Return code descriptions are: \* 0 NO\_ERROR \*385 ERROR\_MOUSE\_NO\_DEVICE \*466 ERROR\_MOUSE\_DETACHED \*501 ERROR\_MOUSE\_NO\_CONSOLE \*505 ERROR\_MOUSE\_EXTENDED\_SG

### Bindings

#### C

```
<PRE> #define INCL_MOUSE
USHORT rc = MouFlushQue(DeviceHandle);
HMOU DeviceHandle; /* Mouse device handle */
USHORT rc; /* return code */ </PRE>
```

#### MASM

```
<PRE> EXTRN MouFlushQue:FAR INCL_MOUSE EQU 1
PUSH WORD DeviceHandle ;Mouse device handle CALL MouFlushQue
Returns WORD </PRE>
```

#### Mou

From:  
<https://osfree.org/doku/> - osFree wiki

Permanent link:  
<https://osfree.org/doku/doku.php?id=en:docs:fapi:mouflushque&rev=1633614871>

Last update: **2021/10/07 13:54**



