

## MouClose

**Bindings:** C, MASM

This call closes the mouse device for the current session.

*MouClose* (**DeviceHandle**)

*DeviceHandle* (**HMOU**) - input Mouse device handle from a previous *MouOpen*.

*rc* (**USHORT**) - return Return code descriptions are:

|          |                        |
|----------|------------------------|
| <b>0</b> | <b>NO_ERROR</b>        |
| 385      | ERROR_MOUSE_NO_DEVICE  |
| 466      | ERROR_MOU_DETACHED     |
| 501      | ERROR_MOUSE_NO_CONSOLE |
| 505      | ERROR_MOU_EXTENDED_SG  |

### Remarks

*MouClose* closes the mouse device for the current session and removes the mouse device driver handle from the list of valid open mouse device handles.

### C bindings

```
#define INCL_MOU

USHORT rc = MouClose(DeviceHandle);

HMOU DeviceHandle; /* Mouse device handle */

USHORT rc; /* return code */
```

### MASM bindings

```
EXTRN MouClose:FAR
INCL_MOU EQU 1

PUSH WORD DeviceHandle ;Mouse device handle
CALL MouClose

Returns WORD
```

From:

<https://www.osfree.ru/doku/> - **osFree wiki**

Permanent link:

<https://www.osfree.ru/doku/doku.php?id=en:ibm:prcp:mou:close>

Last update: **2016/09/15 03:13**

