VioDeRegister

Bindings: C, MASM

This call deregisters a video subsystem previously registered within a session.

VioDeRegister ( )

rc (**USHORT**) - return Return code descriptions are:

0	NO_ERROR
404	ERROR_VIO_DEREGISTER
430	ERROR_VIO_ILLEGAL_DURING_POPUP
465	ERROR_VIO_DETACHED
494	ERROR_VIO_EXTENDED_SG

Remarks

VioDeRegister must be issued by the same process that issued the previous VioRegister. After VioDeRegister is issued, subsequent video calls are processed by the Base Video Subsystem.

C bindings

```
#define INCL_VIO

USHORT  rc = VioDeRegister(VOID);

USHORT           rc;            /* return code */
```

MASM bindings

```
EXTRN  VioDeRegister:FAR
INCL_VIO            EQU 1

CALL   VioDeRegister

Returns WORD
```

From:
http://osfreeorgysalbcqrk3kqib55urra2mvtfmsoezcqwop2fed7jc64gqd.onion/doku/ - **osFree wiki**

Permanent link:
http://osfreeorgysalbcqrk3kqib55urra2mvtfmsoezcqwop2fed7jc64gqd.onion/doku/doku.php?id=en:ibm:prcp:vio:dereg

Last update: **2016/09/14 10:45**